

BEAM CENTRAL VACUUM UNITS



	SC335	SC385 LCD	SC395 LCD	SC3500
Coverage m ²	400	600	700	1000
Max no inlets	7	10	15	25
Furthest inlet	60	90	90	120
Airwatts	590	670	582	868
Suction Power (mm H ₂ O)	2962	3352	3226	3482
Input Power (watts)	1650	1700	1700	3000
ECS Motor	Y	Y	Y	Y
Motor & size (ins)	D 5.7	D 5.7	A 7.2	D 7.2 x 2
Sound level (dB)	62	62	63	66
Height x Diameter (mm)	890 x 280	1065 x 280	1065 X 355	1120 x 355
Weight	13	15	19	27
LCD display	N	Y	Y	N
Dust Canister (litres)	15	15	25	25
Utility Inlet	Y	Y	Y	Y
Self cleaning filter	Y	Y	Y	Y
Dual intake	Y	Y	Y	Y
Exhaust Muffler	Y	Y	Y	Y X 2

LCD display includes system performance, dust bucket check, service reminder, operating hours, time and temperature.

All dust buckets are transparent and anti microbial.

All units have soft start, anti vibration mountings and self cleaning filters.

The SC395 has an Amatek Lamb motor. The others have Domel motors.



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

ELECTROLUX CENTRAL VACUUM UNITS



OXYGEN SERIES



	ZCV845	ZCV860	ZCV870
Coverage m ²	400	600	700
Max no inlets	7	10	15
Furthest inlet	60	90	90
Airwatts	580	675	700
Suction Power (Kpa)	32	34	36
Input Power (watts)	1600	1725	1800
Circuit Amps	10	10	10
Motor 1 Stage TF High Power	Yes	Yes	Yes
Sound level (dB)	67	66	65
Height x Diameter (mm)	930/465/380	1032/465/380	1032/465/380
Weight	8.4	8.7	9
Information display	On/Off LED	Full LED	LCD
Dust Canister (litres)	24	31	31
Utility Inlet	No	No	No
Self cleaning filter	Yes	Yes	Yes
Dual intake	Yes	Yes	Yes
Overheating Safety	Yes	Yes	Yes



Vacrite Limited
 Unit 163 Chiswick High Road
 London
 W4 4HH

0845 467 9197

ASTROVAC CENTRAL VACUUM UNITS



	SR15	SR55	SR65
Coverage m ²	400	1000	1800
Max no inlets	7	8 - 12	13 +
Furthest inlet	40	50	75
Airwatts	600	631	1040
Suction Power (mm H ₂ O)	3600	3600	3100
Input Power (watts)	1400	1900	3120
ECS Motor	-	-	-
Motor & size (ins)	5.7	7.2	5.7 x 2
Sound level (dB)	58	66	74
Height x Diameter (mm)	981 x 362	1060 x 403	1230 x 403
Weight			
LCD display	N	N	N
Dust Canister (litres)	28	43	43
Utility Inlet	Y	Y	Y
Self cleaning filter	Y	Y	Y
Dual intake	N	N	N
Exhaust Muffler	Y	Y	Y

The self cleaning filter is made from Surf-Tex™ and resists bacteria, mould, and mildew growth. This material can also capture particles as small as .3 microns and has a dust retention of 97% efficiency.

The debris is collected in the bottom canister. This canister features our patented air channel that allows the bottom canister to have a liner.



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

VACUMAID CENTRAL VACUUM UNITS



	S650	P73H
Coverage m ²	100	150
Max no inlets	3	5
Furthest inlet	20	25
Airwatts	517	488
Suction Power (mm H ₂ O)	2478	2478
Input Power (watts)	1560	1560
ECS Motor	-	-
Motor & size (ins)	5.1	5.1
Sound level (dB)	66	66
Height x Diameter (mm)	495 X 327	603 X 325
Weight		
LCD display	N	N
Dust Bag (litres)	17	23
Utility Inlet	N	N
Self cleaning filter	N	N
Dual intake	N	N
Exhaust Muffler	Y	Y

These units feature a powerful high airwatt 5.1 single stage through flow motor with sealed paper bag filtration. They are small but powerful, suitable for small homes or apartments. The replaceable dust bag has an inner lining which gives additional strength for a longer life and also serves as an electrostatic barrier. The unit is constructed from rolled galvanized steel and is powder coated for a corrosion resistant lifetime of use.



Vacrite Limited
 Unit 163 Chiswick High Road
 London
 W4 4HH

0845 467 9197

VACUMAID SPLIT SYSTEM CENTRAL VACUUM UNIT



	S3500
Coverage m ²	1800
Max no inlets	14-20
Furthest inlet	90
Airwatts	1268
Suction Power (mm H ₂ O)	3480
Input Power (watts)	3.94
ECS Motor	-
Motor & size (ins)	7.2 x 2
Sound level (dB)	78
Height x Diameter (mm)	514 X 375
Weight	
LCD display	N
Dust Canister (litres)	43
Utility Inlet	N
Self cleaning filter	Y
Dual intake	N
Exhaust Muffler	Y



Separator
1022 X 410

The VacuMaid® split canisters are the most unique central vacuum on the market. With the power unit separate from the dirt canister you can place the two in separate locations. It is best that the power unit be placed in a remote location to further reduce any motor noise and place the dirt canister where it is easily accessible. These units use ultra long life motors for superior performance.

Split canister systems are especially good for people with pets. With the split system most of the hair is collected in the bottom can, but some may make its way to the top screen. This screen can easily be cleaned by removing the top lid and wiping away the hair. With bag systems hair from pets will easily clog the bag reducing its performance and cleaning ability. The bottom cans feature a plastic liner for clean and easy emptying.



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

DISAN CENTRAL VACUUM UNITS



	ZSA 18/1	ZSA 25/1	ZSA 45/2	ZSA45/3
Coverage m ²	90	130	350	500
Max no inlets	5	5	12	15
Furthest inlet	40	40	70	110
Airwatts	341	341	505	552
Suction Power (mm H ₂ O)	2600	2600	3360	3410
Input Power (watts)	1250	1250	1400	1500
EC Safety	IP44	IP44	IP44	IP44
Motor Turbine Stages	2	2	2	3
Sound level (dB)	60	60	61	60
Height x Diameter (cm)	57x32	67x32	125x39	125x39
Weight Kg (with packing)	11.5	12.8	37.2	37.5
LCD display	N	N	N	N
Dust Canister (litres)	15	25	45	45
Utility Inlet	N	N	N	N
Cartridge filter	Y	Y	Y	Y
Dual intake	N	N	N	N
Exhaust Muffler	Y	Y	Y	Y



Vacrite Limited
 Unit 163 Chiswick High Road
 London
 W4 4HH

0845 467 9197

DISAN CENTRAL VACUUM UNITS



	EVO200	EVO500
Coverage m ²	150	400
Max no inlets	5	15
Furthest inlet	45	100
Airwatts	369	523
Suction Power (mm H ₂ O)	2700	3300
Input Power (watts)	1100	1500
EC Safety	IP40	IP40
Motor Turbine Stages	2	2
Sound level (dB)	60	60
Height x Diameter (cm)	92x32	92x32
Weight Kg (with packing)	17.5	18
LCD display	N	N
Dust Canister (litres)	20	20
Utility Inlet	N	N
Cartridge filter	Y	Y
Dual intake	Y	Y
Exhaust Muffler	Y	Y



Vacrite Limited
 Unit 163 Chiswick High Road
 London
 W4 4HH

0845 467 9197

DISAN CENTRAL VACUUM UNITS

HEAVY DOMESTIC, LIGHT COMMERCIAL



SUPER COMPACT AND SUPER COMPACT TURBO

	SC1.5	SCT 2.2	SC Turbo 2.2	SC Turbo 4.5
Power Supply	240v 1ph	240v 1ph	400v 3ph	400v 3ph
Max no operators	1	2	1	2
Furthest inlet m	150	150	200	200
Airwatts	574	688	638	825
Suction Power (mm H ₂ O)	3000	3060	3200	3600
Input Power (watts)	1500	2200	2200	4500
Electronic Inverter	N	N	Y	Y
Brushless Motor	Y	Y	Y	Y
Sound level (dB)	65	68	67	68
W x D x H (cm)	40x54x161	40x54x161	40x54x161	40x54x161
Weight Kg (with packing)	91	94	99	108
Vacuum Gauge	Y	Y	Y	Y
Dust Canister (litres)	70	70	70	70
Utility Inlet	Y	Y	Y	Y
Filter Shaker Manual	Y	Y	Y	Y
Filter Shaker Automatic	Optional	Optional	Optional	Optional
Exhaust Muffler	Optional	Optional	Optional	Optional



Vacrite Limited
 Unit 163 Chiswick High Road
 London
 W4 4HH

0845 467 9197

MD CENTRAL VACUUM UNITS



	M55 Quiet	M45	M85
Coverage m ²	180	500	750
Max no inlets	4	10	10 +
Furthest inlet	30	45	45
Airwatts	419	448	448
Suction Power (mm H ₂ O)	2266	3482	3482
Input Power (watts)	-	-	-
Motor	By Pass	By Pass	Thru Flo
Motor size (ins)	5.7	5.7	5.7
Stages	1	2	3
Height x Diameter (mm)	510 x 360	740 x 360	840 x 360
Weight	12 kg	16 kg	15.5 kg
LCD display	N	N	N
Dust Canister (litres)	22.5	36	36
Utility Inlet	N	N	N
Dirt Bag filter	Y	Y	Y
Dual intake	N	N	N
Exhaust Muffler	N	N	N

Standard features include the finest electrical components (Lamb/Ametec motors, Basler Transformers and Honeywell relays), a 5-stage filtering system (Combining cloth, mesh foam and paper elements), with a large disposal bag .



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

MD CENTRAL VACUUM UNITS



	S44	S4	S5
Coverage m ²	<800	<500	<2000
Max no inlets	15	15	Bespoke
Furthest inlet	60	60	115
Airwatts	653	444	866
Suction Power (mm H ₂ O)	3759	3508	3508
dBA	68	68	62
Motor	By Pass	By Pass	By Pass
Motor size (ins)	5.7	5.7	2 x 5.7
Stages	2	3	3
Height x Diameter (mm)	965 x 360	838 x 360	965 x 360
Weight	19 kg	19 kg	22 kg
LCD display	N	N	N
Dust Canister (litres)	55	55	55
Utility Inlet	Y	Y	Y
Dirt Bag filter	Y	Y	Y
Dual intake	N	N	N
Exhaust Muffler	Y	Y	Y

Standard features include the finest electrical components (Lamb/Ametec motors, Basler Transformers and Honeywell relays), a 5-stage filtering system (Combining cloth, mesh foam and paper elements), with a large disposal bag .



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

GLOBOVAC CENTRAL VACUUM UNITS



Coverage m ²
Max no inlets
Furthest inlet
Airwatts
Air Flow m ³ /hr
dBA
Motor KW
Motor
Water protection rating
Dia/Height (cm)
Weight
LCD display
Dust Canister (litres)
Utility Inlet
Filter (Washable)
Dirt Bag filter *

GV Mini
80
4/5
20
444
190
<60
1.4
Ametek
IP44
30/43
8
No
15
No
Cartridge
Optional

GV 1.4
150
6/7
25
505
205
<60
1.5
Ametek
IP44
30/62
9
No
6
No
Cartridge
Optional

GV 1.6
200
10/12
35
570
240
<60
1.6
Ametek
IP44
30/80
9.2
No
15
No
Cartridge
Optional

* Double filtering system (an exclusive feature of our vacuum units) fits a washable polyester cartridge (primary filter) and a polyester fabric bag filter that prevents saturation of the primary filter, simultaneously guaranteeing very practical and hygienic disposal. Includes adapter and polyester fabric bag– made of special V2 certified self-extinguished polymer.



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197

GLOBOVAC CENTRAL VACUUM UNITS



Coverage m ²
Max no inlets
Furthest inlet
Airwatts
Air Flow m ³ /hr
dBA
Motor KW
Motor
Water protection rating
Dia/Height (cm)
Weight
LED display
Dust Canister (litres)
Utility Inlet
Filter (Washable)
Dirt Bag filter *

GV 1.6 LED
200
10/12
35
570
240
<60
1.6
Ametek
IP44
30/80
9.2
Yes
15
No
Cartridge
Optional

GV 1.9
250
16/19
50
685
270
<55
1.9
Ametek
IP44
30/93
9.5
No
25
No
Cartridge
Optional

GV 1.9 LED
250
16/19
50
685
270
<55
1.9
Ametek
IP44
30/93
9.5
Yes
25
No
Cartridge
Optional

* Double filtering system (an exclusive feature of our vacuum units) fits a washable polyester cartridge (primary filter) and a polyester fabric bag filter that prevents saturation of the primary filter, simultaneously guaranteeing very practical and hygienic disposal. Includes adapter and polyester fabric bag– made of special V2 certified self-extinguished polymer.



Vacrite Limited
Unit 163 Chiswick High Road
London
W4 4HH

0845 467 9197